

2.7.7.2

1. Linux
2. NASNFS)
3. session

(IP)	
master.domain.com	
c1.domain.com	1
c2.domain.com	2

1. ->>:
2. ->>:

Debian NFS

1. portmap, nfs-kernel-server, nfs-common
2. /etc/exports,
/opt/iReport365/app_home/data *(rw,sync,no_root_squash,no_subtree_check)

1. ->>:
2. ->>:
- 3.
4. /opt/iReport365/app_home/conf/db.properties

```
platform.mongodb.host=master.domain.com
platform.mongodb.port=27017
platform.mongodb.dbname=
```

5. :

```
mv /opt/iReport365/app_home/data /opt/iReport365/app_home/data.bak
mount -t nfs master.domain.com:/opt/iReport365/app_home/data
/opt/iReport365/app_home/data
```

6. (

Nginx

```
upstream mbi.domain.com {
    server master.domain.com:8080;
    server c1.domain.com:8080;
    server c2.domain.com:8080;
    ip_hash;
}

server {
    listen      80;
    server_name mbi.domain.com;
    autoindex off;
    index index.do;
    charset utf-8;
    client_max_body_size 300M;
    location ~ / {
        proxy_read_timeout 3600;
        proxy_connect_timeout 3600;
        proxy_pass          http://mbi.domain.com;
        proxy_redirect      off;
        proxy_set_header    Host                $host;
        proxy_set_header    X-Real-IP          $remote_addr;
        proxy_set_header    X-Forwarded-For
$proxy_add_x_forwarded_for;
    }
}
```