-

DebianRedHat64Linux

Google ChromeFirefoxEdgeIE10HTML5
IE

NAS2 /app_home

1.

1		8G50G	Tomcat
2		8G50G	Tomcat
		8G100G	MongoDB+Redis
NAS		100G	2 /app_home
Nginx		4G50G	

2.

https://pan.macochart.com/s/2yHg4af3E63YFyq

2

(1) maco-platform-cluster-xxx.tar.gz Tomcat8JDK1.8war)
(2) maco-datacache-cluster-xxx.tar.gz RedisMongoDB)

:
https://pan.macochart.com/s/4rHGPdjZAoJdGrn

3.

(1) maco-datacache-cluster-xxx.tar.gz /opt/maco-datacache-cluster-xxx.tar.gz
(2)

```
cd /opt
tar xvfz maco-datacache-cluster-xxx.tar.gz
```

(3) MongoDB

```
cd /opt/maco/mongodb
./run.sh
```

(4) Redis

```
cd /opt/maco/redis
./run.sh
```

4. **1**

(1) maco-platform-cluster-xxx.tar.gz 1 /opt/maco-platform-cluster-xxx.tar.gz
(2)

```
cd /opt
tar xvfz maco-platform-cluster-xxx.tar.gz
```

(3) /opt/maco/app_home/conf/system.properties

```
app_home=/app_home
```

(4) /app_home/conf/app.properties

```
#MongoDB, hostport
platform.mongodb.host=x.x.x.x
platform.mongodb.port=27017
#MongoDBreplicaset
platform.mongodb.replicaset=x.x.x.x:27017
#
platform.mongodb.dbname=xxxx
#usernamemongodbusername,password,authdbname
platform.mongodb.username=xxx
platform.mongodb.password=xxx
platform.mongodb.authdbname=xxx

#Redis, hostport
redis.host=x.x.x.x
redis.port=6379
#Redisnodes, masterName
redis.sentinels.nodes=x.x.x.x.:6379
server.redis.sentinel.masterName=erpsentinel
//Redis
redis.database=1
//Redis
redis.password=xxx


#httphttpshttps)
platform.scheme=https
```

(5) Tomcat

```
cd /opt/maco
./run.sh
```

(6) :

```
cd /opt/maco
./taillog.sh
```

(7)
http://x.x.x.x:9090 x.x.x.x

5. **2**

(1) maco-platform-cluster-xxx.tar.gz 2 /opt/maco-platform-cluster-xxx.tar.gz
(2)

```
cd /opt
tar xvfz maco-platform-cluster-xxx.tar.gz
```

(3) /opt/maco/app_home/conf/system.properties

```
app_home=/app_home
```

(4)

```
cd /opt/maco
./run.sh
```

(5) :

```
cd /opt/maco
./taillog.sh
```

(6)
http://x.x.x.x:9090 x.x.x.x

6. **Nginx**

```
upstream platform_server {
        server x.x.x.x:9090;
        server y.y.y.y:9090;
}


server {
        listen       80;
        server_name  mbi.xxx.com;
        autoindex off;
        index index.do;
        charset utf-8;
        client_max_body_size 300M;

        location ~ / {
                proxy_read_timeout 3600;
                            proxy_connect_timeout 3600;
                            proxy_pass      http://platform_server;
                            proxy_redirect  off;
                            proxy_set_header        Host
$host;
                            proxy_set_header        X-Real-IP
$remote_addr;
                            proxy_set_header        X-Forwarded-For
$proxy_add_x_forwarded_for;
                            proxy_set_header X-Forwarded-Proto
$scheme;
                                proxy_http_version 1.1;
                                proxy_set_header Upgrade
$http_upgrade;
                                proxy_set_header Connection "upgrade";

        }

    }
```

1.x.x.x.x:9090 1IPTomcat9090
2. y.y.y.y:9090 2IPTomcat9090
3. mbi.xxx.com