

DebianRedHat64Linux

Google ChromeFirefoxEdgeIE10HTML5
IE

1.

		8G50G	DMZTomcat
		8G100G	MongoDB+RedisDMZ
		8G50G	DMZ

2.

<http://pan.macochart.com/index.php/s/dCk5mNikyZ63Cmm>

2

- (1) maco-platform-xxx.tar.gz
- (2) maco-datacache-xxx.tar.gz
- (3) maco_client_linux_x64_xxx.zip

3.

<http://pan.macochart.com/index.php/s/8CMZTNJesfCCJ5M>

1war

- (1) maco-clientmode-x.x.x.war

4.

- (1) maco-datacache-xxx.tar.gz /opt/maco-datacache-xxx.tar.gz
- (2)

```
cd /opt
tar xvfz maco-datacache-xxx.tar.gz
```

- (3) MongoDB

```
cd /opt/maco/mongodb
./run.sh
```

- (4) Redis

```
cd /opt/maco/redis
./run.sh
```

5.

(1) maco-platform-xxx.tar.gz 1 /opt/maco-platform-xxx.tar.gz

(2)

```
cd /opt
tar xvfz maco-platform-xxx.tar.gz
```

(3) /opt/maco/app_home/conf/system.properties

```
app_home=/opt/maco/app_home
```

(4) /opt/maco/app_home/conf/db.properties

```
#IPMongoDBx.x.x.xIP
platform.mongodb.host=x.x.x.x
platform.mongodb.port=27017
```

(5) /opt/maco/app_home/conf/redis.properties

```
#IPRedisx.x.x.xIP
redis.host=x.x.x.x
redis.port=6379
```

(6) Tomcat

```
cd /opt/maco
./run.sh
```

(7) :

```
cd /opt/maco
./taillog.sh
```

(8)

http://x.x.x.x:9090 x.x.x.x

6.

- Linux

7.

(1) `maco_client_linux_x64_xxx.zip /opt/maco_client_linux_x64_xxx.zip`

(2)

```
cd /opt
unzip maco_client_linux_x64_xxx.zip
```

(6) Tomcat

```
cd /opt/maco
./run.sh
```

(7)

<http://x.x.x.x:9090> x.x.x.x