

Redis

(1)

```
${}/maco.war/WEB-INF/classes/clientmode/spring-data-redis.xml
```

11

```
<bean id="redisConnectionFactory"
class="org.springframework.data.redis.connection.jedis.JedisConnectionFactory">
    <property name="hostName" value="#{redisProp['redis.host']}" />
    <property name="port" value="#{redisProp['redis.port']}" />
</bean>
```

```
<bean id="redisConnectionFactory"
class="org.springframework.data.redis.connection.jedis.JedisConnectionFactory">
    <property name="hostName" value="#{redisProp['redis.host']}" />
    <property name="port" value="#{redisProp['redis.port']}" />
    <!-- Redis -->
    <property name="password" value="#{redisProp['redis.password']}" />
</bean>
```

(2)

```
${}/maco.war/WEB-INF/classes/security-service.xml
```

147

```
<bean id="redisManager" class="org.crazycake.shiro.RedisManager">
    <property name="host" value="#{redisProp['redis.host']}" />
    <property name="port" value="#{redisProp['redis.port']}" />
</bean>
```

```
<bean id="redisManager" class="org.crazycake.shiro.RedisManager">
  <property name="host" value="#{redisProp['redis.host']}" />
  <property name="port" value="#{redisProp['redis.port']}" />
  <property name="password" value="#{redisProp['redis.password']}" />
</bean>
```

(3)

```
${app_home}/conf/redis.properties
```

:

```
redis.password=${redis}
redis.database=0
```

(4)